BEST AVAILABLE COPY

20030159.ORI

-

IN THE CLAIMS

1	1. (currently amended) A hole former for a manhole with an invert comprising:
2	an invert-mold having an invert pipe portion with a tube-aligned on the central axis of
3	the invert pipe portion,
4	a hole former having an alignment member with an aperture along the length of the
5	central axis through the alignment member,
6	an invert mold having an invert pipe portion with a tube having an aperture aligned on
7	the central axis of the invert pipe portion, the tube extending through a portion of the invert
8	pipe portion a sufficient distance such that when the central axis through the alignment
9	member is aligned with the tube in the invert mold a desirably aligned hole in the manhole
0	results for making pipe connections thereto,
1	a bar for inserting in the aperture of the alignment member and the invert mold tube
2	for aligning the hole former with the invert mold.
1	2.(original) A hole former for a manhole with an invert as in claim 1 wherein,
2	the alignment member and hole former are integral.
	3. (previously presented) A hole former for a manhole with an invert as in claim 1
?	wherein,
;	the alignment member and hole former are aligned by a female portion on the hole
	former mating with a male portion on a spacer.

BEST AVAILABLE COPY

20030159.ORJ

- 4. (previously presented) A hole former for a manhole with an invert as in claim 3
- 2 wherein,
- a threaded portion of the bar engages a threaded portion of the tube to secure the hole
- 4 former to the invert mold.
- 1 5. (previously presented) A hole former for a manhole with an invert as in claim 1
- 2 wherein,
- 3 the alignment member has a spacer portion for displacing the hole former from the
- 4 invert mold pipe portion and mating therewith.